

HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

📞 +90 216 364 15 00 🔹 🖂 export@gbl.com.tr 🔹 🌐 www.gbl.com.tr

# SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006

Surgical Instrument Disinfectant: Peracetic Acid, Concentrated

# 1. Identification of the substance/mixture and of the company/undertaking:

# 1.1. Product identifiers

Product Name	: Surgical Instrument Disinfectant; Peracetic Acid, Concentrated	
Trademark	: PEROXY™ HLD	
Product Ref No	: 6128	

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

High-level disinfectant / Cold sterilant for surgical, medical, endoscopic, thermosensitive equipment and medical devices. Active against spores of bacteria.

# 1.3. Detailers of the supplier of the safety data sheet:

**Company Name** : GBL Gül Biyoloji Laboratuvarı Sanayi ve Ticaret Anonim Şirketi

Address : HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Ümraniye İstanbul

TÜRKİYE

Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775

34775 Ümraniye İstanbul TÜRKİYE

Telephone : +90 216 364 15 00
Fax : +90 216 314 15 69
E-mail : export@gbl.com.tr

# 1.4. Emergency telephone number:

Company: +90 216 364 15 00

or contact your local emergency telephone number.

# 2. Hazard identification:

#### 2.1. Classification of the substance or mixture:

# Classification according to Regulation (EC) No 1272/2008

Oxidizing liquid, Category 2; H272

Acute toxicity, Category 4; H302

Skin corrosive, Category 1A; H314

Specific target organ toxicity, Single exposure, Category 3; H335

For the full text of the H-statements mentioned in this Section, see Section 16.

# 2.2. Label Elements

# Labeling according to Regulation (EC) No 1272/2008

Pictogram





Doc. No: SDS EN 6128 1/9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

📞 +90 216 364 15 00 • 🔀 export@gbl.com.tr • 🌐 www.gbl.com.tr

Signal word : Danger

Hazard statement(s)

H272: May intensify fire; oxidizer.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation. Precautionary statement(s) :

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.

P260: Do not breathe dust/fume/gas/mist/vapors/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P405: Store locked up.

P410: Protect from sunlight.

Supplemental Hazard Statements : None.

2.3. Other hazards: None.

# 3. Composition/information of ingredients:

# 3.1. Substance:

Not applicable.

#### 3.2. Mixture:

Component	Classification	Concentration
Hydrogen Peroxide, 50% CAS No: 7722-84-1 EC No: 231-765-0	Ox. Liq. 2; H272 Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 45 - < 55 %
Acetic Acid, 80% CAS No: 64-19-7 EC No: 200-580-7	Flam. Liq. 3 H226 Skin Corr. 1A, H314	>= 10 - < 14 %

For the full text of the H-statements mentioned in this Section, see Section 16.

#### 4. First aid measures:

# 4.1. Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

Doc. No: SDS EN 6128 2 / 9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

🕻 +90 216 364 15 00 • 🔀 export@gbl.com.tr • 🌐 www.gbl.com.tr

Remove the victim into fresh air. Immediately consult a doctor/medical service.

# In case of skin contact

Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Remove clothing before washing. Consult a doctor/medical service.

#### In case of eye contact

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.

#### If swallowed

Rinse mouth with water. Give nothing to drink. Do not induce vomiting. Immediately consult a doctor/medical service. Take the container/vomit to the doctor/hospital.

# 4.2. Most important symptoms and effects, both acute and delayed

No data available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

#### 5. Firefighting measures:

# 5.1. Extinguishing media

# Suitable extinguishing media

Water spray.

# Unsuitable extinguishing media

No data available.

# 5.2. Special hazards arising from the substance or mixing

No data available.

#### 5.3. Advice for firefighters

Special protective masks and protective clothing should be worn during firefighting. Use selfcontained breathing apparatus.

#### 5.4. Further information

No data available.

# 6. Accidental release measures:

# 6.1. Personal precautions, protective equipment, and emergency procedures

Avoid contact with eyes and skin. Wear full face mask, plastic boots, and plastic gloves. Avoid substance contact. Make sure there is good ventilation. Do not breathe waste. For personal protection see section 8.

#### 6.2. Environmental precautions

Do not let the product enter drains.

# 6.3. Methods and materials for containment and cleaning up

Stop leaks if possible. Dilute spillage with water spray as far as necessary to reduce hazard. Contain runoff by any means available. Do not use plugs made from organic material like wood, to stop leaks. If substance has entered a watercourse or sewer, inform the

Doc. No: SDS EN 6128 3/9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

📞 +90 216 364 15 00 • 🔀 export@gbl.com.tr • 🌐 www.gbl.com.tr

responsible authority. Ventilate sewers and basements where there is no risk to personnel or the public.

#### 6.4. Reference to other sections

For disposal see section 13.

#### 7. Handling and storage:

#### 7.1. Precautions for safe handling

Wear personal protective equipment. Avoid contact with eyes. Make sure there is good ventilation. Avoid direct contact with the substance. Do not approach sources of ignition or smoke. Keep away from sources of ignition - No smoking. For precautions see section 2.2.

# 7.2. Conditions for safe storage, including any incompatibilities

Ensure adequate and good ventilation. The tank must be cool and dry. Smoking, eating and drinking should be prohibited in the environment. Store the substance/preparation in its original container. Do not store together with metals. Keep away from flammable materials, heat, and ignitors.

For the recommended storage temperature, see the product label.

## 7.3. Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

# 8. Exposure controls/personal protection:

# 8.1. Control parameters

Hydrogen Peroxide, 50% [CAS No: 7722-84-1]:

OSHA PEL: 1 ppm (1,4 mg/m³) TWA NIOSH REL: 1 ppm (1,4 mg/m³) TWA Acetic Acid, 80% [CAS No: 64-19-7]: OSHA PEL: 10 ppm (25mg/m³) TWA

#### 8.2. Exposure controls

#### **Appropriate engineering controls**

Wash hands before breaks and immediately after handling the product.

#### Personal protective equipment

*Eye/face protection:* Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dust.

Skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

*Body protection:* Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Doc. No: SDS EN 6128 4/9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

📞 +90 216 364 15 00 • 🔀 export@gbl.com.tr • 🌐 www.gbl.com.tr

Respiratory protection: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let the product enter drains.

# 9. Physical and chemical properties:

# 9.1. Information on basic physical and chemical properties

Appearance Liquid Color Colorless.

Odor No data available.
Odor threshold No data available.

pH < 2

Melting point

Boiling point

No data available.

Flash point

No data available.

Evaporation rate

No data available.

Flammability

No data available.

Upper/lower flammability or explosive

No data available.

limits

Vapor pressure No data available. Vapor density No data available. Density No data available. Water solubility No data available. Partition coefficient: n-octanol/water No data available. Auto-ignition temperature No data available. No data available. Viscosity **Explosive properties** No data available. No data available. Oxidizing properties

# 9.2. Other safety information

No data available.

# 10. Stability and reactivity:

# 10.1. Reaction

No data available.

# 10.2. Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

Avoid contact with alkalis, amines, strong acids, and metals.

Doc. No: SDS EN 6128 5/9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

📞 +90 216 364 15 00 • 🖂 export@gbl.com.tr • 🌐 www.gbl.com.tr

#### 10.4. Conditions to avoid

Open flame. Overheating.

# 10.5. Incompatible materials

Oxidizing agents, strong reducing agents.

Combustible materials; heavy metals. such as iron, copper, chromium, nickel, aluminum and cobalt.

# 10.6. Hazardous decomposition products

Oxygen.

#### 11. Toxicological information:

# 11.1. Information on toxicological effects

# **Acute toxicity**

Hydrogen Peroxide, 50% [CAS No: 7722-84-1]:

LD50 intraperitoneal – mouse – 800 mg/kg

LD50 Oral – mouse – 2000 mg/kg

LD50 Skin - mouse - 12000 mg/kg

LD50 Oral - rabbit - 820 mg/kg

LD50 Oral - rat - 910 mg/kg

LD50 Skin - rat - 4060 mg/kg

Acetic Acid, 80% [CAS No: 64-19-7]:

LD50 Oral - rat - 3310 mg/kg

LD50 Skin - rabbit - 1060 mg/kg

Skin corrosion/irritation

Causes severe skin burns.

Serious eye damage/eye irritation

Causes severe eye damage.

Respiratory or skin sensitization

No data available.

Carcinogenicity

No data available.

**Reproductive Toxicity** 

No data available.

Specific target organ toxicity - single exposure

No data available.

Specific target organ toxicity - repeated exposure

No data available.

**Aspiration hazard** 

No data available.

# 11.2. Additional information

No data available.

Doc. No: SDS EN 6128 6/9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

+90 216 364 15 00 • 🖂 export@gbl.com.tr • 🌐 www.gbl.com.tr

# 12. Ecological information:

## 12.1. Toxicity

<u>Hydrogen Peroxide, 50% [CAS No: 7722-84-1]</u>:

LC50/96 h Pimephales promelas: 16.4 mg/L

LC50/72 h Leuciscus idus: 35 mg/L EC50/48 h Daphnia pulex: 2.4 mg/L EC50/24 h Daphnia magna: 7.7 mg/L

EC50/72 h Skeletonema costatum: 1.38 mg/L

Acetic Acid, 80% [CAS No: 64-19-7]:

LC50/96 h Oncorhynchus mykiss: > 300.8 mg/L LC50/96 h Lepomis macrochirus: 75 mg/L EC50/24 h Daphnia magna: 47 mg/L

## 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Other adverse effects

No data available.

# 13. Disposal considerations:

# 13.1. Waste treatment methods:

Waste materials must be disposed of in accordance with Directive 2008/98/EC and other National and Local Regulations. Leave chemicals in original containers. Do not mix with other waste. Treat uncleaned containers as the product itself.

# **14.**Transport information:

ADR/RID

ADR/RID Class : 5.1
UN Number : 3149
Packaging Group : II

Propper Shipping Name : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE

with acid(s), water and not more than 5% peroxyacetic acid,

**STABILIZED** 

**Label** : 5.1+8

Doc. No: SDS EN 6128 7/9



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

y, budding out main, interest block sous sk. 110.20 1.0.. 347/3 officially establish forkers





Tunnel Code : E

**IMDG** 

IMDG Class : 5.1 UN Number : 3149 Packaging Group : II

Propper Shipping Name : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE

with acid(s), water and not more than 5% peroxyacetic acid,

**STABILIZED** 

**EmS** : F-H; S-Q

# ICAO/IATA

Forbidden for transported by air.

# 15. Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

# 15.2. Chemical safety assessment

For this product, a chemical safety assessment was not carried out.

# 16.Other information:

#### **Revision Information**

Document No: SDS EN 6128 First Issue Date: 07.09.2023 Revision Date/No: -/00

#### Full text of H-statements referred to under sections 2 and 3.

H226 Flammable liquid and vapor.
H272 May intensify fire; oxidizer.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage
H318 Causes serious eye damage.

H412 Harmful to aquatic life with long-lasting effects.

May cause respiratory irritation.

Doc. No: SDS EN 6128 8/9

First Issue Date: 04.09.2023 / Rev No: 00

H335



HQ: Serifali Mah. Hattat Sk. No:10 P.O.: 34775 Umraniye Istanbul TURKIYE Factory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

ctory: Dudullu OSB Mah. IMES C Blok 305 Sk. No:16 P.O.: 34775 Umraniye Istanbul TURKIYE

📞 +90 216 364 15 00 • 🔀 export@gbl.com.tr • 🌐 www.gbl.com.tr

#### **Abbreviations:**

ADR European Agreement concerning the International Carriage of Dangerous Goods

by Road

CAS No Chemical Abstracts Service number

EC No European Inventory of Existing Commercial Chemical Substances

EC50 Effective concentration, 50 percent

EmS Emergency Schedule

IATA International Air Transport AssociationICAO International Civil Aviation OrganizationIMDG International Maritime Dangerous Good

LC50 Lethal concentration, 50 percent

LD50 Lethal dose, 50 percent

NIOSH National Institute for Occupational Safety and Health

OSHA Occupational Safety and Health Administration

PBT Persistent, Bio-accumulative and Toxic

PEL Permissible exposure limit
REL Recommended exposure limit

RID International Carriage of Dangerous Goods by Rail

STEL A short-term exposure limit
TWA Time-weighted average

vPvB Very Persistent and very Bio-accumulative

**Notice to Reader:** The information contained herein in accurate to the latest knowledge and describes the product from the point of view of help and environmental protection as well as safe handling. The information presented in this SDS refers to the technical product only and will not apply to any processed product. Final determination of suitability of any materials is the sole responsibility of the user.

Doc. No: SDS EN 6128 9/9